



螺纹钢产品

| 品种 Varieties | 规格 Specification | 代表钢号或等级 Steel No. Or Grade | 执行标准 Product standards |
|------------------------------|---------------------|--|---|
| 螺纹钢 Hot rolled ribbed bar | Φ12~Φ32 | HRB400/HRB400E 40【280】、60【420】、75【520】、80【550】 B500A、B500B、B500C | GB1499-1998 BS4449-2005-EN ASTM-A615&615M-2004a |
| 螺纹钢 Hot rolled ribbed bar | Φ12~Φ32 | HRB500/HRB500E 40【280】、60【420】、75【520】、80【550】 B500A、B500B、B500C | GB1499-1998 BS4449-2005-EN ASTM-A615&615M-2004a |



无缝钢管 seamless steel pipes

| 品种 Varieties | 规格 (D×S) mm Specification(D*S)mm | 代表钢号或等级 Steel No. Or Grade | 执行标准 Product standards |
|---|-------------------------------------|--|---|
| 套管 Casting pipes | 114.3~177.8×5.21~22.22 | J55、N80-1、N80Q、R95、 L80-1、C90、P110、Q125 | API 5CT |
| 油管 Oil tubing pipes | 48.3~114.3×3.68~16 | J55、N80、L80、P110、 Q125、L80-13Cr、L80-9Cr | API 5CT |
| 钻杆 Drilling pipes | 60.3~168.3×6.45~12.7 | E75、X95、G105、S135 | API 5DP |
| 管线管 Line pipes | 60.3~168.3×3.6~25 | X42-X80 | API 5L |
| 流体输送管 Fluid conveying pipes | 48~180×3.5~25 | 10、20、09MnV、16Mn、 Q345B | GB/T8163-2008 |
| 结构管 Structural pipes | 48~180×3.5~25 | 10、20、45、27、27SiMn、 20CrMo、30CrMo | GB/T8163-2008 |
| 高压锅炉管 High pressure boiler pipes | 48~180×4~25 | 20G、15CrMoG、 2Cr1MoVG、T91、P91、 P11、P22 | ASME SA335M ASME SA213M |
| 石油裂化管 Oil cracking pipes | 60~180×5~25 | 20、12CrMo、15CrMo | GB 9948-2006 |
| 高压化肥管 High pressure fertilizer pipes | 48~168×5~25 | 20、16Mn、12CrMo、 15CrMo | GB 6479-2000 |
| 中低压化肥管 Low-medium pressure fertilizer pipes | 48~168×3.5~20 | 10、20 | GB 3087-2008 |
| 液压支柱管 Hydraulic pillar pipes | 68~180×6~25 | 20、35、27SiMn | GB/T17396-2009 |
| 气瓶管 Gas cylinder pipes | 89~180×4.5~8 | 30CrMo、35CrMo、 34Mn2V、37Mn | JIS G3429 GB 18248-2008 ASTM A519 |

